

Material Safety Data Sheet

Colored Acryl

Section 1 - Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: COLORED POLYMERS

Chemical Name: N/A

Family: ACRYLIC POLYMER

Product Use: NAIL POLYMER

Product #: various

MSDS Approval

Date: 11/29/2000

MSDS Prepared by: BSQ

Manufacturer: ABC International Sp. z o.o.

Ul. Odolańska 10 Warszawa 02-560

Emergency Phone Numbers: (0048)42 631 47 24

Information Contacts: (0048)228800455

Section 2 - Composition/Information on Ingredients

Chemical Identity	CAS #	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL		
Poly (ethyl methacrylate)	9003-42-3	N/E	Polyethylmethacrylate	N/E	N/E	Not Listed	65-99
Poly (methyl methacrylate)	9011-14-7	N/E	Polymethyl Methacrylate	N/E	N/E	Group 3/no/no	0-35
Titanium Dioxide	13463-67-7	236-675-5	Titanium dioxide/CI77891	15 mg/m3	10 mg/m3	Group 3/no/no	0-1
Dibenzoyl Peroxide	94-36-0	202-327-6	Benzoyl peroxide	5 mg/m3	5 mg/m3	3/no/no	0-1

May Contain the following: Please see Section 16 for additional compounds

N/E - None Established

N/DA - No Data Available

This product is not considered hazardous by OSHA Hazard Communication Standard.

N/R - Not Reviewed

N/A - Not Applicable

Hazard Symbols: Xi Risk Phrases: R36/37/38 Safety Phrases: S18, S22, S24/25, S38

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- May cause allergic skin reaction.
- May cause eye irritation.
- Dust may cause irritation of the nose, throat, and lungs.
- This product may contain particulate, not otherwise classified (Nuisance Dust)

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Eyes or skin (No absorption); inhalation of dust.

Eye Higher concentration can irritate eyes. May cause eye irritation or damage.

Skin Repeated or prolonged exposure may cause allergic skin rashes.

Ingestion Higher concentration can irritate respiratory system.

Inhalation Possible temporary discomfort due to inhalation of dust concentration above the permissible exposure limit. Dust may cause irritation of the nose, throat, and lungs.

Sub-Chronic Effects For Polymer: OSHA classifies this material as Particulates, Not Otherwise Classified. Eyes, skin and Respiratory tract may be irritated by gross overexposure to Particulates, Not Otherwise Classified, no matter how they are generated. Avoid inhalation of dust. Keep dust out of eyes to prevent possible irritation.
For decomposition product: Methyl Methacrylate Monomer; Liquid or high vapor concentration can irritate eyes, respiratory system and cause skin rashes. Prolonged exposure can lead to headaches, nausea, staggering gait, confusion, drowsiness and unconsciousness. Repeated and prolonged over exposure may cause permanent brain and nervous system damage, allergic skin rashes, eye corrosion and permanent injury, as well as changes in liver and kidney function or damage.
For Benzoyl Peroxide: repeated or prolonged contact may cause skin sensitization.

NOTE: Refer to Section 11, Toxicological Information for Details

Section 4 - First Aid Measures

First Aid for Eye Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.

First Aid for Skin Wash with soap and water. Get medical help if discomfort persists.

First Aid for Inhalation Remove to fresh air. Get medical help if discomfort persists.

Material Safety Data Sheet

Colored Acryl

First Aid for Ingestion Rinse mouth out with water. Call doctor if amount was large.

Section 5 - Fire Fighting Measures

Flash Point (°F/°C) TAG Closed: 580°F/304°C	Flammable Limit (vol%) N/A	Auto-ignition Temperature (vol%) N/E
--	-------------------------------	---

Method:
Extinguishing Media: Water, carbon dioxide, dry chemical.

Fire Fighting Instructions: Avoid extinguishing methods that generate dust clouds. Water streams can disperse dust into air, producing a fire hazard and possible explosion hazard. Fire-fighters should wear self-contained breathing apparatus.

Unusual Hazards: Polymer dust is combustible, explosive limits of the polymer particles suspended in air are approximately those of coal dust.

Section 6 - Accidental Release Measures

Spill or Release Procedures Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills.

Section 7 - Handling and Storage

Handling Observe precautions found on the label. Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking. Avoid prolonged or repeated contact with skin. Avoid contamination. Use only with adequate ventilation.

Storage Store in cool, dry place away from heat, sparks, flame and direct sunlight. Close container after each use. Ground all metal containers when transferring. Use explosion-proof equipment. Store away from combustibles and incompatible materials.

Explosion Hazard Polymer dust is combustible, explosive limits of the polymer particles suspended in air are approximately those of coal dust.

Section 8 - Exposure Controls / Personal Protective Equipment

Engineering Controls Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers. High temperature processing equipment should be well ventilated. Use explosion-proof equipment. Provide ventilation if necessary to control exposure levels below airborne exposure limits.

Personal Protective Equipment

General	Dust collectors are recommended for handling powder in bulk.
Eye/ Face Protection	Use safety glasses and have eye flushing equipment immediately available.
Skin Protection	Minimize contamination by following good industrial practice. Wearing nitrile, neoprene, pvc, latex or other impermeable gloves is recommended.
Respiratory Protection	Avoid breathing dust and mist. Use dust mask.

Section 9 - Physical and Chemical Properties

Appearance Fine, white powder	Odor & Odor Threshold Faint odor in bulk.	pH N/A	Specific Gravity N/A	Viscosity N/A	% Volatile N/A		
Boiling Point/ Freezing Point N/A	Decomposition Temperature N/A	Octanol/Water Partitioning Coefficient Log Po/w N/A	Vapor Pressure: N/A	Vapor Density N/A	Evaporation Rate N/A	Ignition N/A	Solubility In Water (20°C) insoluble
Flash Point (°F/°C) TAG Closed: 580°F/304°C	Flammable Limit (vol%) N/A	Auto-ignition Temperature (vol%) N/E					

Section 10 - Stability and Reactivity

Stability: Incompatibility (Materials to Avoid):
Stable Strong oxidizing agents

Hazardous Decomposition Products: Hazardous Polymerization: Conditions to Avoid:

Material Safety Data Sheet

Colored Acryl

methacrylate monomers will not occur Heating above 240 deg C , 464 deg F

Section 11 - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
LD50 Oral (Rat) : 7990mg/kg	LD50 Dermal (Rabbit): 35,500 mg/kg	LC50 Inhalation (Rat) : >12,500 to 16,500 ppm for 0.5 hours	mild	mild

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the copolymers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
No information available	No information available	No information available

RTECS#: 9011-14-7; TR0400000

Section 12 - Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
Flathead minnows and goldfish TLm24 : 420 ppm Bluegills TLm24 : 368 ppm	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13 - Disposable Considerations

May be disposed of in a landfill or incinerated. Follow Federal, State and Local regulations for disposal. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14 - Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Non-Regulated Material
Identification Number:	N/A
Marine Pollutant:	No
Special Provisions:	N/A
Emergency Response Guidebook (ERG) #:	N/A
IATA (DGR):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Packaging Instructions:	
Emergency Response Guidance (ICAO)#:	
IMO (IMDG):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Special Provisions & Stowage/Segregation:	None
Emergency Schedule (EmS)#:	
Other Information:	Flash point > 100°C

Section 15 - Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP's) or ozone depleting substances (ODS's), as defined by the U. S. Clean Air Act: • NONE
------------------------	--

Material Safety Data Sheet


Colored Acryl

Clean Water Act: Priority Pollutant	This product contains the following chemicals listed under the U.S. Clean Water Act Priority Pollutant List: • NONE
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is not considered a hazardous chemical under the OSHA Hazard Communication Standard.
RCRA	This product contains no chemicals considered to be hazardous waste under RCRA (40 CFR 261).
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Sec. 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List).
SARA Title III: Section 311-312:	This product does not contain hazardous substances under the OSHA Hazard Communication Standard, and is not regulated under Section 311-312 (40 CFR 370).
SARA Title III: Section 313:	This product contains the following chemicals outlined in SARA Title III: Section 313: • Benzoyl Peroxide CAS #94-36-0.
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Benzoyl Peroxide CAS #94-36-0
NJ Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Benzoyl Peroxide CAS #94-36-0
PA Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Benzoyl Peroxide CAS #94-36-0
FL Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0
MN Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Benzoyl Peroxide CAS #94-36-0


International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Polymethyl methacrylate CAS# 9011-14-7 is on the DSL List. WHMIS = n/da Polyethylmethacrylate CAS# 9003-42-3 is on the DSL List. WHMIS = n/da Titanium Dioxide CAS #13463-67-7, WHMIS = Not controlled. Benzoyl Peroxide CAS #94-36-0 is on the DSL list. WHMIS = C, D2B, B4
EINECS: European Inventory: 	Colored Polymers: • HAZARD SYMBOLS: Xi: Irritant • RISK PHRASES: R36/37/38: Irritating to eyes, respiratory system and skin • SAFETY PHRASES: S18: Handle and open container with care, S22: do not breath dust, S24/25: avoid contact with skin and eyes, S38: in case of insufficient ventilation, wear suitable respiratory equipment.


Section 16 - Other Information

Hazard Rating System (Pictograms)

NFPA:



HMIS:



* - Respiratory protection may be necessary depending on conditions of use. Refer to Section VIII of this MSDS for respiratory

Material Safety Data Sheet

Colored Acryl

protection guidelines.

MAY CONTAIN THE FOLLOWING CHEMICALS:

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
FD&C Blue #1	3844-45-9	N/E	Blue 1/CI42090	N/E	N/E	Not Listed	0-1
Yellow No.4	1934-21-0	217-699-5	Yellow 5/CI19140	N/E	N/E	Not Listed	0-1
D&C Red #7	5281-04-9	N/E	Red 7/CI15850	N/E	N/E	Not Listed	0-1
D&C Red #30	2379-74-0	219-163-6	Red 30/CI13360	N/E	N/E	Not Listed	0-1
D&C Orange #5	596-03-2	209-876-0	Orange 5/CI45370	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
Iron Oxide Black	1317-61-9	215-277-5	Iron Oxide/CI77489	N/E*	N/E*	Not Listed	0-1
Red Iron Oxide	1382-37-2	215-570-8	Iron Oxide/CI77491	N/E*	N/E*	Not Listed	0-1
Yellow Iron Oxide	51274-00-1	N/E	Iron oxides/CI77492	N/E	N/E	Not Listed	0-1
Mica	12001-26-2	N/E	Mica	N/E	3 mg/m ³	Not listed	0-1

N/E - None Established N/DA-No Data Available

N/R - Not Reviewed N/A-Not Applicable

OSHA PEL for nuisance dust: 15 mg/m³ (total dust)
5 mg/m³ (respirable dust)

ACGIH PEL for nuisance dust: 10 mg/m³

Revised Sections since Last Version: Updated section 2 contents, section 16 contents and overall format update

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (0048)42 631 47 24.